

# Package ‘mrap’

December 8, 2025

**Title** Machine-Readable Data Analysis Results with Function Wrappers

**Version** 1.0.1

**Description** You can use the set of wrappers for analytical schemata to reduce the effort in writing machine-readable data. The set of all-in-one wrappers will cover widely used functions from data analysis packages.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.2.3

**URL** <https://gitlab.com/TIBHannover/lki/knowledge-loom/mrap-r>

**BugReports** <https://gitlab.com/TIBHannover/lki/knowledge-loom/mrap-r/-/issues>

**Imports** dtreg, jsonlite, stringr

**Suggests** knitr, lme4, rmarkdown, testthat (>= 3.0.0)

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Olga Lezhnina [aut] (ORCID: <<https://orcid.org/0000-0003-2237-7725>>),  
Manuel Prinz [aut] (ORCID: <<https://orcid.org/0000-0003-2151-4556>>),  
Markus Stocker [aut, cre] (ORCID:  
<<https://orcid.org/0000-0001-5492-3212>>),  
Open Research Knowledge Graph Project and Contributors [cph]

**Maintainer** Markus Stocker <markus.stocker@tib.eu>

**Repository** CRAN

**Date/Publication** 2025-12-08 13:30:02 UTC

## Contents

|                                |   |
|--------------------------------|---|
| algorithm_evaluation . . . . . | 2 |
| class_discovery . . . . .      | 3 |
| class_prediction . . . . .     | 3 |
| correlation_analysis . . . . . | 4 |

|                                  |           |
|----------------------------------|-----------|
| data_analysis . . . . .          | 5         |
| descriptive_statistics . . . . . | 5         |
| factor_analysis . . . . .        | 6         |
| group_comparison . . . . .       | 7         |
| multilevel_analysis . . . . .    | 7         |
| regression_analysis . . . . .    | 8         |
| stats_aov . . . . .              | 9         |
| to_jsonld . . . . .              | 9         |
| <b>Index</b>                     | <b>11</b> |

---

|                      |                                         |
|----------------------|-----------------------------------------|
| algorithm_evaluation | Create an algorithm_evaluation instance |
|----------------------|-----------------------------------------|

---

**Description**

Create an algorithm\_evaluation instance

**Usage**

algorithm\_evaluation(code\_string, input\_data, named\_list\_results)

**Arguments**

- code\_string      A line of code as a string, or "N/A" if not given
- input\_data      A data frame, a named list, or a URL as a string
- named\_list\_results  
                  A named list with metrics and values

**Value**

An algorithm\_evaluation instance

**Examples**

```
res <- list(F1= 0.46, recall = 0.51)
inst_ae <- algorithm_evaluation("N/A", "data_url", res)
```

---

|                 |                                   |
|-----------------|-----------------------------------|
| class_discovery | Create a class_discovery instance |
|-----------------|-----------------------------------|

---

**Description**

Create a class\_discovery instance

**Usage**

```
class_discovery(code_string, input_data, test_results)
```

**Arguments**

|              |                                                   |
|--------------|---------------------------------------------------|
| code_string  | A line of code as a string, or "N/A" if not given |
| input_data   | A data frame, a named list, or a URL as a string  |
| test_results | A data frame or a list of data frames             |

**Value**

A class\_discovery instance

**Examples**

```
clust_data <- iris[-5]
res <- data.frame(result_1 = 1, result_2 = 2)
inst_cd <- class_discovery(
  "stats::kmeans(clust_data, 3)",
  iris,
  res
)
```

---

|                  |                                    |
|------------------|------------------------------------|
| class_prediction | Create a class_prediction instance |
|------------------|------------------------------------|

---

**Description**

Create a class\_prediction instance

**Usage**

```
class_prediction(code_string, input_data, test_results)
```

**Arguments**

|              |                                                   |
|--------------|---------------------------------------------------|
| code_string  | A line of code as a string, or "N/A" if not given |
| input_data   | A data frame, a named list, or a URL as a string  |
| test_results | A data frame or a list of data frames             |

**Value**

A class\_prediction instance

**Examples**

```
res <- data.frame(result_1 = 1, result_2 = 2)
inst_cp <- class_prediction(
  "stats::glm(Species ~ Petal.Width + Petal.Length, family='binomial', iris)",
  iris,
  res
)
```

---

correlation\_analysis    *Create a correlation\_analysis instance*

---

**Description**

Create a correlation\_analysis instance

**Usage**

```
correlation_analysis(code_string, input_data, test_results)
```

**Arguments**

|              |                                                   |
|--------------|---------------------------------------------------|
| code_string  | A line of code as a string, or "N/A" if not given |
| input_data   | A data frame, a named list, or a URL as a string  |
| test_results | A data frame or a list of data frames             |

**Value**

A correlation\_analysis instance

**Examples**

```
res <- data.frame(result_1 = 1, result_2 = 2)
inst_ca <- correlation_analysis(
  "stats::cor.test(iris$Petal.Length, iris$Sepal.Length)",
  iris,
  res
)
```

---

|               |                                 |
|---------------|---------------------------------|
| data_analysis | Create a data_analysis instance |
|---------------|---------------------------------|

---

**Description**

Create a data\_analysis instance

**Usage**

```
data_analysis(instances, code_reference = NULL)
```

**Arguments**

instances      Analytic instance or a list of instances  
code\_reference   A URL of the code implementing data analysis

**Value**

A data analysis instance

**Examples**

```
res <- data.frame(mean = 3.758)
inst_ds <- descriptive_statistics(
  "base::mean(iris$Petal.Length)",
  iris,
  res
)
inst_da <- data_analysis(inst_ds)
```

---

|                        |                                          |
|------------------------|------------------------------------------|
| descriptive_statistics | Create a descriptive_statistics instance |
|------------------------|------------------------------------------|

---

**Description**

Create a descriptive\_statistics instance

**Usage**

```
descriptive_statistics(code_string, input_data, test_results)
```

**Arguments**

code\_string      A line of code as a string, or "N/A" if not given  
input\_data       A data frame, a named list, or a URL as a string  
test\_results     A data frame or a list of data frames

**Value**

A descriptive\_statistics instance

**Examples**

```
res <- data.frame(mean = 3.758)
inst_ds <- descriptive_statistics(
  "base::mean(iris$Petal.Length)",
  iris,
  res
)
```

---

|                 |                                   |
|-----------------|-----------------------------------|
| factor_analysis | Create a factor_analysis instance |
|-----------------|-----------------------------------|

---

**Description**

Create a factor\_analysis instance

**Usage**

```
factor_analysis(code_string, input_data, test_results)
```

**Arguments**

|              |                                                   |
|--------------|---------------------------------------------------|
| code_string  | A line of code as a string, or "N/A" if not given |
| input_data   | A data frame, a named list, or a URL as a string  |
| test_results | A data frame or a list of data frames             |

**Value**

A factor\_analysis instance

**Examples**

```
fa_data <- iris[-5]
res <- data.frame(result_1 = 1, result_2 = 2)
inst_fa <- factor_analysis(
  "stats::princomp(fa_data)",
  iris,
  res
)
```

---

|                  |                                    |
|------------------|------------------------------------|
| group_comparison | Create a group_comparison instance |
|------------------|------------------------------------|

---

**Description**

Create a group\_comparison instance

**Usage**

```
group_comparison(code_string, input_data, test_results)
```

**Arguments**

|              |                                                   |
|--------------|---------------------------------------------------|
| code_string  | A line of code as a string, or "N/A" if not given |
| input_data   | A data frame, a named list, or a URL as a string  |
| test_results | A data frame or a list of data frames             |

**Value**

A group\_comparison instance

**Examples**

```
res <- data.frame(result_1 = 1, result_2 = 2)
inst_gc <- group_comparison(
  "stats::aov(Petal.Length ~ Species, data = iris)",
  iris,
  res
)
```

---

|                     |                                       |
|---------------------|---------------------------------------|
| multilevel_analysis | Create a multilevel_analysis instance |
|---------------------|---------------------------------------|

---

**Description**

Create a multilevel\_analysis instance

**Usage**

```
multilevel_analysis(code_string, input_data, test_results)
```

**Arguments**

|              |                                                   |
|--------------|---------------------------------------------------|
| code_string  | A line of code as a string, or "N/A" if not given |
| input_data   | A data frame, a named list, or a URL as a string  |
| test_results | A data frame or a list of data frames             |

**Value**

A multilevel\_analysis instance

**Examples**

```
code_string <- "lme4::lmer(math ~ homework + (1 | schid))"
res <- data.frame(result_1 = 1, result_2 = 2)
inst <- multilevel_analysis(code_string, "data_url", res)
```

---

|                     |                                       |
|---------------------|---------------------------------------|
| regression_analysis | Create a regression_analysis instance |
|---------------------|---------------------------------------|

---

**Description**

Create a regression\_analysis instance

**Usage**

```
regression_analysis(code_string, input_data, test_results)
```

**Arguments**

|              |                                                   |
|--------------|---------------------------------------------------|
| code_string  | A line of code as a string, or "N/A" if not given |
| input_data   | A data frame, a named list, or a URL as a string  |
| test_results | A data frame or a list of data frames             |

**Value**

A regression\_analysis instance

**Examples**

```
res <- data.frame(result_1 = 1, result_2 = 2)
inst_ra <- regression_analysis(
  "stats::lm(Petal.Length ~ Sepal.Length, data = iris)",
  iris,
  res
)
```



---

|           |                                 |
|-----------|---------------------------------|
| stats_aov | <i>Wrap stats::aov function</i> |
|-----------|---------------------------------|

---

**Description**

Wrap stats::aov function

**Usage**

```
stats_aov(...)
```

**Arguments**

... the same arguments as in the wrapped function

**Value**

a list of ANOVA object and R6 class instance

**Examples**

```
results <- stats_aov(Petal.Length ~ Species, data = iris)
```

---

|           |                                            |
|-----------|--------------------------------------------|
| to_jsonld | <i>Write an instance in JSON-LD format</i> |
|-----------|--------------------------------------------|

---

**Description**

This function is imported from dtreg for ease-of-use

**Usage**

```
to_jsonld(instance)
```

**Arguments**

instance An instance of an R6 class

**Value**

JSON string in JSON-LD format

**Examples**

```
res <- data.frame(mean = 3.758)
inst_ds <- descriptive_statistics(
  "base::mean(iris$Petal.Length)",
  iris,
  res
)
json <- to_jsonld(inst_ds)
```

# Index

algorithm\_evaluation, [2](#)  
class\_discovery, [3](#)  
class\_prediction, [3](#)  
correlation\_analysis, [4](#)  
data\_analysis, [5](#)  
descriptive\_statistics, [5](#)  
factor\_analysis, [6](#)  
group\_comparison, [7](#)  
multilevel\_analysis, [7](#)  
regression\_analysis, [8](#)  
stats\_aov, [9](#)  
to\_jsonld, [9](#)