

The trip package

Michael D. Sumner

2013

Abstract

The **trip** package provides tools for working with animal track data.

1 Introduction

Basic use of the trip package.

2 Data input and validation

```
> library(trip)
> d <- data.frame(x = 1:10, y = rnorm(10), tms = Sys.time() + 1:10,
+   id = gl(2, 5))
> coordinates(d) <- ~x + y
> proj4string(d) <- CRS("+proj=laea")
> tr <- trip(d, c("tms", "id"))
> summary(tr)
```

Object of class trip

	tripID ("id")	No.Records	startTime ("tms")	endTime ("tms")	tripDuration
1	1	5	2013-08-25 07:48:50	2013-08-25 07:48:54	4 secs
2	2	5	2013-08-25 07:48:55	2013-08-25 07:48:59	4 secs

	tripDistance	meanSpeed	maxSpeed	meanRMSspeed	maxRMSspeed
1	6.216637	5594.974	6523.260	1161.7033	4646.813
2	4.358589	3922.731	4349.153	987.4362	3949.745

Total trip duration: 8 seconds (0 hours, 8 seconds)

Derived from Spatial data:

Object of class SpatialPointsDataFrame

Coordinates:

	min	max
--	-----	-----

x	1.000000	10.000000
---	----------	-----------

y	-1.409579	1.351959
---	-----------	----------

Is projected: TRUE

proj4string : [+proj=laea]

Number of points: 10

Data attributes:

	tms	id
Min.	:2013-08-25 17:48:50	1:5
1st Qu.	:2013-08-25 17:48:52	2:5
Median	:2013-08-25 17:48:54	

```
Mean    :2013-08-25 17:48:54  
3rd Qu.:2013-08-25 17:48:56  
Max.    :2013-08-25 17:48:59
```

3 Simple plotting

```
> plot(tr)  
> lines(tr)
```





Figure 1: Plot of a very simple trip object.

4 Gridding for time spent

```
> tg <- tripGrid(tr)  
> image(tg, col = c("transparent", heat.colors(25)))
```



5 Example data from diveMove