Package 'rapsimng.decide'

November 23, 2026

Title Decision-Oriented Analysis Interface for APSIM Next Generation Outputs

Version 0.1.2

Description Provides a high-level interface for analysing Agricultural Production Systems sIMulator ('APSIM') Next Generation simulation outputs to support structured decision-making workflows. The package coordinates domain-specific decision modules (e.g. cultivar selection, experimental design) and standardises their outputs into reproducible decision reports. It does not perform 'APSIM' simulations or implement decision logic directly, but serves as an orchestration layer connecting analysis results with reporting and downstream interpretation.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 4.1.0)

Suggests testthat (>= 3.0.0)

Imports rlang, rapsimng.decide.core (>= 0.1.2), rapsimng.decide.cultivar (>= 0.1.2), rapsimng.decide.sowing (>= 0.1.2), rapsimng.decide.nitrogen (>= 0.1.2)

Config/testthat/edition 3

URL https://decide.rapsimng.bangyou.me/, https://github.com/byzheng/rapsimng.decide

BugReports https://github.com/byzheng/rapsimng.decide/issues

Config/roxygen2/version 8.1.1

NeedsCompilation no

Author Bangyou Zheng [aut, cre]

Maintainer Bangyou Zheng <zheng.bangyou@gmail.com>

Repository CRAN

Date/Publication 2026-11-23 07:40:16 UTC

Contents

document 2
evaluate 4

Index 6

`document` *Document a Decision From APSIM NG Outputs*

Description

`document()` is a high-level orchestration wrapper for decision workflows built on APSIM Next Generation outputs. It validates inputs, dispatches to a domain-specific decision package, and standardises the returned result into a common report structure. It does not implement the decision logic itself.

Usage

```
document(
  data,
  decision,
  context = list(),
  criteria = list(),
  options = list(),
  simplify = FALSE,
  ...
)
```

Arguments

`data`	A data frame or tibble containing APSIM Next Generation simulation outputs.
`decision`	A single string identifying which decision workflow to run, such as `"cultivar"`.
`context`	A named list of contextual inputs supplied to the selected decision workflow.
`criteria`	A named list of decision criteria or thresholds used by the selected decision workflow.
`options`	A named list of additional options that control reporting or documentation behaviour in the selected decision workflow.
`simplify`	A boolean flag indicating whether to simplify the returned document into a character vector of lines. If `FALSE`, the full structured document is returned.
`...`	Additional arguments passed through to the domain-specific decision documenter.

Details

This package separates responsibilities across the wider workflow:

- `rapsimng` is responsible for running or preparing APSIM Next Generation simulations and outputs.
- `rapsimng.decide.*` packages implement domain-specific decision logic, such as cultivar suitability assessment.

- downstream analysis or interpretation layers, including packages such as agrillm, can consume the standardised report returned here.

rapsimng.decide sits between these layers and provides a consistent entry point and output contract for decision-oriented reporting.

Value

A list with class "rapsimng_decide_report" containing four named components:

- meta: metadata describing the decision context and execution.
- metrics: summary metrics produced by the decision workflow.
- tables: tabular outputs ready for reporting.
- figures: figure objects, specifications, or references for visual output.

Examples

```
example_data <- data.frame(
  Cultivar = c("A", "A", "B", "B"),
  Year = c(2020, 2021, 2020, 2021),
  SowingDOY = c(120, 120, 125, 125),
  Flowering = c(200, 201, 202, 203),
  Yield = c(4000, 4200, 3800, 3900),
  FrostReduction = 0,
  HeatReduction = 0,
  FrostEvent = 0,
  HeatEvent = 0
)
decision_context <- list(vars = list(
  cultivar_col = "Cultivar",
  year_col = "Year",
  sowing_col = "SowingDOY",
  flower_col = "Flowering",
  yield_col = "Yield",
  frost_reduction_col = "FrostReduction",
  heat_reduction_col = "HeatReduction",
  frost_event_col = "FrostEvent",
  heat_event_col = "HeatEvent"
))
report <- document(
  data = example_data,
  decision = "cultivar",
  context = decision_context,
  simplify = TRUE
)
head(report)
```

`evaluate` *Evaluate a Decision From APSIM NG Outputs*

Description

`evaluate()` is a high-level orchestration wrapper for decision workflows built on APSIM Next Generation outputs. It validates inputs, dispatches to a domain-specific decision package, and standardises the returned result into a common report structure. It does not implement the decision logic itself.

Usage

```
evaluate(
  data,
  decision,
  context = list(),
  criteria = list(),
  options = list(),
  ...
)
```

Arguments

`data`	A data frame or tibble containing APSIM Next Generation simulation outputs.
`decision`	A single string identifying which decision workflow to run, such as `"cultivar"`.
`context`	A named list of contextual inputs supplied to the selected decision workflow.
`criteria`	A named list of decision criteria or thresholds used by the selected decision workflow.
`options`	A named list of additional options that control reporting or evaluation behaviour in the selected decision workflow.
`...`	Additional arguments passed through to the domain-specific decision evaluator.

Details

This package separates responsibilities across the wider workflow:

- `rapsimng` is responsible for running or preparing APSIM Next Generation simulations and outputs.
- `rapsimng.decide.*` packages implement domain-specific decision logic, such as cultivar suitability assessment.
- downstream analysis or interpretation layers, including packages such as `agrillm`, can consume the standardised report returned here.

`rapsimng.decide` sits between these layers and provides a consistent entry point and output contract for decision-oriented reporting.

Value

A list with class "rapsimng_decide_report" containing four named components:

- meta: metadata describing the decision context and execution.
- metrics: summary metrics produced by the decision workflow.
- tables: tabular outputs ready for reporting.
- figures: figure objects, specifications, or references for visual output.

Examples

```
example_data <- data.frame(
  Cultivar = c("A", "A", "B", "B"),
  Year = c(2020, 2021, 2020, 2021),
  SowingDOY = c(120, 120, 125, 125),
  Flowering = c(200, 201, 202, 203),
  Yield = c(4000, 4200, 3800, 3900),
  FrostReduction = 0,
  HeatReduction = 0,
  FrostEvent = 0,
  HeatEvent = 0
)
decision_context <- list(vars = list(
  cultivar_col = "Cultivar",
  year_col = "Year",
  sowing_col = "SowingDOY",
  flower_col = "Flowering",
  yield_col = "Yield",
  frost_reduction_col = "FrostReduction",
  heat_reduction_col = "HeatReduction",
  frost_event_col = "FrostEvent",
  heat_event_col = "HeatEvent"
))
report <- evaluate(
  data = example_data,
  decision = "cultivar",
  context = decision_context
)
names(report)
```

Index

document, 2

evaluate, 4